



INTERIOR ACOUSTICS
VERTIFACE®
DATASHEET

X
E
E
E
E



W
E
L
C
O
M
E

VERTIFACE®

Vertiface® is our most versatile product. It is literally the face of some of our most well known products like Composition® and Symphony® and can be added to our Quitespace® Panel so that they match your unique design ideas. But you may decide you want to use it to make lampshades or cover your furniture because it is one of the most durable, hard wearing and UV resistant fabrics in the market today.

So, if you have inherited some tired acoustic applications and want to change their colour or improve their look, Vertiface is the perfect tool to upcycle what you've got, matching it to a new interior or giving it a new lease on life.

You can cut to any shape, creating something as unique as each one of us. It's highly durable and takes everything you can throw at it giving you the assurance of longevity.

APPLICATIONS

- Decorative and functional textile wallcovering for education, commercial offices, theatres, libraries, retail, and hospitality sectors
- Hook-and-loop receptive surface for education and commercial sectors
- Use in conjunction with other Autex Interior Acoustic products

SPECIFICATION:

(Wall) treatment shall be Autex Vertiface® from non-woven needle-punched polyester containing not less than 80% recycled material as manufactured by Autex www.autexindustries.com

Roll 3-4mm (nom.) depth, colour (L), Fire Rating ISO 9705: Classification: Group 1-S, AS ISO 9705 – 2003 Classification: Group 1, EN13501-1:2007+A1:2009: B - s1, d2

Install as per Autex recommendations.

If Vertiface is to be specified for use other than as a wallcovering, please seek guidance from your Autex Account Manager.



W
A

PRODUCT SPECIFICATIONS

Product Name	Vertiface®
Composition	100% Polyester Fibre (PET)
Roll Dimensions	1.3m x 50m Other widths are available on request, minimum order quantity applies
Tolerance	(+5mm) x (+10mm)
Thickness (nom.)	3-4mm
Weight	Typically 380gsm
Finish	Available in fine velour

Hook-and-Loop

Hook-and-loop receptive surface.
A hook of 1.5mm or less is recommended.

INSTALLATION

Install as per Autex recommendations.
If Vertiface is to be specified for use other than as a wallcovering, please seek guidance from your Autex Account Manager.

FASTNESS TO LIGHT

Vertiface is suitable for indoor use only.
Light reflective values below are measured in accordance with BS 8493:2008+A1:2010.

LIGHT REFLECTIVE VALUES BY COLOUR

Civic	57
Citrus	49
Myst	42
Sanz	36
Wasabi	33
Lime	29
Azure	24
Silver	23
Jade	22
Porcelain	22
Fawn	20
Clay	20
Granny Smith	20
Stonewash	19
Simba	18
Brilliant Orange	15
Spearmint	13
Calypso	13
Electric Blue	12
Koala	12

Avocado	11
Blush	10
Sage	9
Emerald	8
Sapphire	8
Atlantis	8
Blazing Red	8
Raspberry	8
Vintage	6
Chilli Red	5
Cinder	5
Bark	5
Octane	5
Phantom	4
Theatre	3
Stately	3
Charcoal	3
Lightsout	3
Ink	3
Noir	1



AUTEX INDUSTRIES

FIRE RATINGS

ISO 9705: 1993

Classification: Group 1-S
Smoke Production Rate: <5.0m²/s
As required by NZBC C/VM2

AS ISO 9705 - 2003

Classification: Group 1
(SMOGRARC): <100m²/s²
Assessed using methodology AS ISO 9705:2003 in accordance with AS 5637.1:2015, as required by BCA Specification C1.10-4 FI 4906 dated 11th July, 2012 and FAR 4055-2 dated 8th October, 2013

EN13501-1:2007+A1:2009

B - s1, d2
WF 336910 dated 25th February, 2014

VOC EMISSIONS

Autex polyester has been tested by Cetec Pty Ltd (Report: CV170908) for chemical emission and is classified as low VOC.
VOC concentration: 0.009 mg/m³ (7 days)

MOISTURE ABSORPTION

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture and will not rot or deteriorate in intended use situations.

PATTERN REPEAT

Non-woven. No pattern repeat but product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up which is an inherent feature of this product.

FABRIC CARE

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution.

ENVIRONMENTAL

Autex is committed to best practice through our ISO 9001 and ISO 14001 certified Quality and Environmental Management systems.

Vertiface products contains a minimum of 80% recycled polyester fibre (from PET bottle-flake). Off-cuts and manufacturing waste is re-used or recycled wherever possible.

Uncontaminated Vertiface can be recycled. For further information, please call Autex on 0800 428 839.

Vertiface is manufactured from 100% polyester fibres and does not contain formaldehyde binders. Autex polyester fibres support safer indoor air quality and will not become a potential airborne pollutant.

SERVICE

For further information about Vertiface or any other Autex product, please contact your Autex Account Manager or visit our website.

Vertiface® is a trademark of Autex Industries Limited and Autex Pty. Vertiface is proudly manufactured in New Zealand by Autex Industries Ltd.



Autex Industries

COLOUR OPTIONS

WASABI	LIME	JADE	GRANNY SMITH
AVOCADO	SPEARMINT	SAGE	AZURE
EMERALD	OCTANE	SAPPHIRE	STONEWASH
STATELY	ATLANTIS	ELECTRIC BLUE	PORCELAIN
INK	LIGHTSOUT	CHARCOAL	NOIR



FA
B
I
E
K

COLOUR OPTIONS

 <p>RASPBERRY</p>	 <p>BRILLIANT ORANGE</p>	 <p>CITRUS</p>	 <p>CINDER</p>
 <p>BLAZING RED</p>	 <p>SIMBA</p>	 <p>CLAY</p>	 <p>BARK</p>
 <p>THEATRE</p>	 <p>CHILLI RED</p>	 <p>VINTAGE</p>	 <p>KOALA</p>
 <p>PHANTOM</p>	 <p>CALYPSO</p>	 <p>MYST</p>	 <p>SILVER</p>
 <p>BLUSH</p>	 <p>FAWN</p>	 <p>SANZ</p>	 <p>CIVIC</p>